

COMPATIBLE POWER SUPPLIES

| SERIES | PART NUMBERS | | SPECIFICATION OVERVIEW | DOWNLOADS |
|----------------------------|---------------|--|---|--------------------------|
| Meanwell PWM Series | PWM-40-24 | | <ul style="list-style-type: none"> - Universal AC Input / Full Range (up to 305VAC) - Constant Voltage PWM Style Output - Built-In 3 in 1 Dimming Function (0-10Vdc or PWM Signal or Resistance) - Dimming Range: 0~100% - Class 2 Power Unit - Suitable for Dry / Damp / Wet Locations - UL Recognized component, 5-Years Warranty | PWM-40-24 SPEC & INSTALL |
| | PWM-40-24 | | | PWM-60-24 SPEC & INSTALL |
| | PWM-90-24 | | | PWM-40-24 SPEC & INSTALL |
| Lutron Hi-Lume Premier | L3D0-96W24V-U | | <ul style="list-style-type: none"> - UL Listed Enclosure - Dimming Range: 100% to 1% and 0.1% - LED Lighting Turns on to Any Dimmed Level Without Flashing to Full Brightness - Operating Voltage: 120V~ to 277V ~ at 50/60 Hz - Rated Lifetime of 50,000 Hours at 40°C (104°F) Ambient Temperature and Maximum Loading - For Rated Warranty, Ambient Temperature not to Exceed 40°C (104°F) - Open-Circuit Protected Output | SPEC SHEET |
| | | | | INSTALLATION GUIDE |

CONTROL MODULES (Requires Additional Auxiliary Non-Dimming Power Supply)

| SERIES | | PART NUMBERS | SPECIFICATION OVERVIEW | DOWNLOADS |
|---------------------|--|-------------------------|---|-----------------------|
| EidoLED Modules | | Linear Drive 200D-D2Z1D | - DALI2 DT6, 1 x 8A, 24DC, Constant Voltage | 200D-D2Z1D SPEC SHEET |
| | | Linear Drive 200D-D2Z2C | - DALI2 DT8, 1 x 4A, 24DC, Constant Voltage | 200D-D2Z2C SPEC SHEET |
| | | Linear Drive 200D-D2Z2D | - DALI2 DT6, 2 x 8A, 24DC, Constant Voltage | 200D-D2Z2D SPEC SHEET |
| | | Linear Drive 180D | - DMX Module – RGB, RGBW & Tuneable White | 180D SPEC SHEET |
| | | Linear Drive 212D | - DMX Module – Static White & Colors | 212D SPEC SHEET |

